probst

max. 200 kg/440 lbs



VS-140/200



VS-140/200



VS-140/200-XL

111222 Technical data comained in this cardague can be modified without prior notice in the interest of pragress. Illustrations are exemplary and non-binding. No fichility accepted for any misprints, mistakes and errors.

SPEEDY VS

Vacuum Hand Laying Device

The powerful single phase powered vacuum turbine also allows the quick and safe handling of very porous material as well as material with exposed aggregate surface. With an integrated suction plate for up to 50 kg (110 lbs) and quick change function. With this new hand laying tool all kinds of slabs can be layed quickly and above all, ergonomically.

Using the quick-change function, all new standard suction plates can be attached in seconds without tools.

Plug type F, 230 V.

- Can, when combined with the corresponding suction plate and lifting eye VS-EH safely lift and lay elements weighing up to 200 kg (441 lbs).
- Existing VS-SPS suction plates can be used via the optionally available VS-GH-SPS retrofit kit.
- I Handles can be rotated 90° by repositioning 2 bolts. This can be of an advantage when switching from crosswise to lengthwise laying of slabs or when the slabs are laid touching a wall.
- Now with unlockable actuating lever for vacuum release. This double safety device secures the paving material against accidental release.
- The working load limit with handles is 140 kg (309 lbs).
- Quick positive suction action (0.5 sec).
- Handles individually height adjustable. Important for users of different heights and for laying steps.
- I Two short handles (in lower position) make easier the taking-off from high stacks of slabs.
- I The handles can be folded down for easy transportation.
- Light weight design.
- Durable surface protection by galvanizing.

VS-140/200-XL:

- With long handles for safe installation of slabs.
- With lifting eye and safety chain for risk-free lifting and handling.





Туре	Description	Dimensions L x W mm (in)	Type of Drive electric/AC (50 Hz) kW	Type of Drive electric/AC (60 Hz) kW	Electric Voltage /AC (50 Hz) V	Electric Voltage /AC (60 Hz) V	Dead Weight kg (lbs)	Working Load Limit/ WLL -200 mbar kg (lbs)	Order-Number
VS-140/200	incl. suction plate 50 kg (110 lbs)	300 x 250 (11.81 x 9.84)	1.5		230		24 (53)	200 (441)	52700015
VS-140/200-XL	incl. suction plate 50 kg (110 lbs) with long handle and lifting eye	300 x 250 (11.81 x 9.84)	1.5		230		30 (66)	200 (441)	52700016
VS-140/200-110	incl. suction plate 50 kg (110 lbs)	300 x 250 (11.81 x 9.84)		1.5		110	24 (53)	200 (441)	52700019
VS-140/200-XL- 110	incl. suction plate 50 kg (110 lbs) with long handle and lifting eye	300 x 250 (11.81 x 9.84)		1.5		110	30 (66)	200 (441)	52700020

Accessories:

Туре	Description	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order - Number
VS-EH	Lifting eye with safety chain for VS-140 and VS-140/200	3.54 (7.80)	200 (441)	42710143
VS-140-XL-HG	Pair of long handles for VS-140/200 for slabs up to 1,2 m width	9 (20)	140 (309)	42710089



SPEEDY POWER-RACK VS-PR

Holder for practical storing of the EU 22i Honda generator when operating the SPEEDY on lifting equipment (e.g. a digger).

- VS-PR is simply hung on the carrying device with adjusted generator (not included in the scope of delivery).
- The VS-EH (not included in the scope of delivery) lifting eye of the SPEEDY is then hung on the eye hook of the VS-PR.
- In the case of a carrying device with a large lifting height, the eye hook may be connected to the VS-EH lifting eye with the 2 m long loop supplied. Thus, first the SPEEDY then the VS-PR can be switched off.
- Incl. 3 m/118 inch (extension cable + Velcro strap.
- Durable surface protection by galvanizing.

VS-PR

Туре	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order-Number
VS-PR	10 (22)	200 (441)	42710166